




UNCONTROLLED DOCUMENT



RECOMMENDED PANEL CUT-OUT



RECOMMENDED PANEL THICKNESS 1.50+0.10/0.00 [0.059+0.004/0.000]

*UNLESS OTHERWISE SPECIFIED TOLERANCES PER DECIMAL PRECISION ARE: X=±1 (±0.039), X.X=±0.5 (±0.020), X.XX=±0.25 (±0.010), X.XXX=±0.127 (±0.005). LEAD SIZE=±0.05 (±0.002), LEAD LENGTH=±0.75 (±0.030), MIN.=+0.00/-0.00 DECIMAL PRECISION MAX.=+0.00/-0.00 DECIMAL PRECISION

PART NUMBER
IFL-EB5138139-22REV.
C

REV.	E.C.N. NUMBER AND REVISION COMMENTS	DATE
A	E.C.N. #10545. CHANGED CASE.	8-10-99
B	E.C.N. #10628.	6-5-00
C	E.C.N. #11148.	12.22.06

ELECTRICAL SPECIFICATIONS

OPERATING VOLTAGE VAC. OR VDC.	12.0-14.0V
DESIGN VOLTAGE VAC. OR VDC.	14.0V
CURRENT DRAW @ DESIGN VOLTS	140mA
M.S.C.P. @ 13.8V (MINIMUM)	0.65 M.S.C.P.
M.S.C.P. @ 13.8V (MAXIMUM)	1.00 M.S.C.P.
AVERAGE LIFE @ DESIGN VOLTS (AC)	7,000 HOURS

MECHANICAL SPECIFICATIONS

BULB SIZE & SHAPE	T5mm TUBULAR
BULB GLASS TYPE	K 12 SOFT GLASS
BASE OR LEAD FINISH	GRAY NYLON 66, 15% GLASS
FILAMENT SHAPE	C-2F

ENVIRONMENTAL SPECIFICATIONS

VIBRATION TESTING	MIL-E-5400N, GRAPH IV
SHOCK TEST	MIL-STD-883 METHOD 2002
	TEST CONDITION A
OPERATION TEMP.	- 50 TO +100 °C
STORAGE TEMP.	- 50 TO +125 °C
SOLDERABILITY OF LEADS	MIL-STD 202F, METHOD 208D



UNCONTROLLED DOCUMENT

REV.
CPART NUMBER
IFL-EB5138139-22T-5mm (T-1 3/4) NEO-WEDGE LAMP, 0.65 M.S.C.P.,
14V, 140mA, WITH TWIST AND LOCK EXTENDED BASE.

CONFIDENTIAL INFORMATION
THE INFORMATION CONTAINED IN THIS DOCUMENT IS THE PROPERTY OF LUMEX INC. EXCEPT AS SPECIFICALLY AUTHORIZED IN WRITING BY LUMEX INC., THE HOLDER OF THIS DOCUMENT SHALL KEEP ALL INFORMATION CONTAINED HEREIN CONFIDENTIAL AND SHALL PROTECT SAME IN WHOLE OR IN PART FROM DISCLOSURE AND DISSEMINATION TO ALL THIRD PARTIES.

RELIABILITY NOTE
OUR MANY YEARS OF EXPERIENCE DATA ACCUMULATION INDICATE THAT SOLDER HEAT IS A MAJOR CAUSE OF EARLY AND FUTURE FAILURE. PLEASE PAY ATTENTION TO YOUR SOLDERING PROCESS.



290 E. HELEN ROAD
PALATINE, IL 60067-6976
PHONE: +1.847.359.2790
US WEB: www.lumex.com
TW WEB: www.lumex.com.tw

DRAWN BY: JC	CHECKED BY:	APPROVED BY:	DATE: 2.22.99
			PAGE: 1 OF 1
			SCALE: N/A

AMEYA360

Components Supply Platform

Authorized Distribution Brand :



Website :

Welcome to visit www.ameya360.com

Contact Us :

➤ Address :

401 Building No.5, JiuGe Business Center, Lane 2301, Yishan Rd
Minhang District, Shanghai , China

➤ Sales :

Direct +86 (21) 6401-6692

Email amall@ameya360.com

QQ 800077892

Skype ameyasales1 ameyasales2

➤ Customer Service :

Email service@ameya360.com

➤ Partnership :

Tel +86 (21) 64016692-8333

Email mkt@ameya360.com