


GU256X128C-3900B

SIMPLIFIED DATASHEET

■ Features

Compact size 256x128
dot fine-pitch VFD.
Smaller dot size, for
showing finely detailed
display patterns.

■ Physical dimension



Get full specification



Click here to go to
request form.

Specifications

■ Electrical Ratings

Parameter	Symbol	Min.	Typ.	Max.	Unit	Condition
Power supply voltage	VCC	4.75	5.00	5.25	VDC	

■ Electrical Characteristics

Parameter	Symbol	Min.	Typ.	Max.	Unit	Condition
Parallel I/F						
Logic input current	I _{PIH}	-	-	1.0	μADC	-
D0-D7, /WR	I _{PIH}	-	-	-200	μADC	-
Logic input voltage	V _{PIH}	0.8VCC	-	VCC	VDC	-
D0-D7, /WR	V _{PIH}	0	-	0.2VCC	VDC	-
Logic output voltage	V _{POH}	3.5	-	VCC	VDC	I _{OH} =-10 μA
RDY	V _{POL}	0	-	0.6	VDC	I _{OL} =4mA
RS-232 I/F						
Logic input voltage	V _{SIH}	3	-	15	VDC	-
RXD, DSR	V _{SIL}	-15	-	-3	VDC	-
Logic output voltage	V _{SOH}	5	-	-	VDC	RL=3KΩ
RXD, DSR	V _{SOL}	-	-	-5	VDC	-
Logic input Impedance	R _{SIH}	3	-	7	KΩ	-
General-purpose I/O port						
Power Supply Current 1	ICC1	-	0.85	1.1	ADC	All dots ON
Power Supply Current 2	ICC2	-	0.68	0.89	ADC	All dots OFF
Power Supply Current 3	ICC3	-	70	120	mADC	Display power OFF
Power Consumption		-	4.25	5.5	W	All dots ON

■ Optical Specifications

Parameter	
Luminance	250 cd/m ² Min. (500 cd/m ² Typ.)
Color of illumination	Green (Blue-Green)

■ Environmental Specifications

Parameter	
Operating Temperature	-40 ~ +85 degrees celsius
Storage Temperature	-40 ~ +85 degrees celsius
Operating Humidity	20 ~ 80% R.H. (non-condensing)
Vibration (non-operating)	10-55-10Hz, all amplitude 1mm, 30 minutes, X-Y-Z
Shock (non-operating)	392m/s ² (40G) 9ms X-Y-Z, 3 times each direction

■ Physical Specifications

Parameter	
Number of Dots	32,768 (256 x 128)
Display Area	83.1 mm x 41.5 mm
Dot Size (X x Y)	0.225 mm x 0.225 mm
Dot Pitch (X x Y)	0.325 mm x 0.325 mm
Weight	About 177 g

■ Interface

Parallel(CMOS), Asynchronous Serial (RS232), I/O port

■ Pin Assignment

Pin No.	Signal	Pin No.	Signal
1	D7	2	D6
3	D5	4	D4
5	D3	6	D2
7	D1	8	D0
9	GND	10	/WR
11	GND	12	RDY
13	GND	14	GND
15	VCC	16	VCC

(Asynchronous Serial)

Pin No.	Signal	Baud Rate Setting
1	RXD	4800bps
2	DTR	9600bps
3	DSR	19200bps
4	TXD	38400bps*
5	TEST	57600bps
6	VCC	115200bps
7	GND	(*:Default setting)

(General-purpose I/O port:Abbreviation)

■ Selectable Font

Parameter	
ANK	All Font Size
International	6 x 8 / 8 x 16 / 12 x 24 / 16 x 32 dot
2-byte character	16 x 16 dot
Japanese	32 x 32 dot
Character numbers	42 x 16 by 6 x 8 dot ASCII
	21 x 5 by 12 x 24 dot ASCII
	16 x 8 by 16 x 16 dot 2-byte character
	8 x 4 by 32 x 32 dot Japanese

■ Functions

Parameter	
Variable Character display	Variable Action Commands
Scroll function	Line / BOX Draw
Display Power Auto ON/OFF	AND/OR/XOR Mixture display
User Windows function	Program Macro function
I/O Port Control Function	Graphic DMA mode
Bit image by dot	
Variable stored settings	
etc.	



Leaflet contents, and specifications and external appearance of products, may change without notice.

Please confirm product details in the specification.

(C)Copyright NORITAKE ITRON CORP.

AMEYA360

Components Supply Platform

Authorized Distribution Brand :



Website :

Welcome to visit www.ameya360.com

Contact Us :

➤ Address :

401 Building No.5, JiuGe Business Center, Lane 2301, Yishan Rd
Minhang District, Shanghai , China

➤ Sales :

Direct +86 (21) 6401-6692
Email amall@ameya360.com
QQ 800077892
Skype ameyasales1 ameyasales2

➤ Customer Service :

Email service@ameya360.com

➤ Partnership :

Tel +86 (21) 64016692-8333
Email mkt@ameya360.com