

High Voltage Isolator

OPI1268

Features:

- TTL compatible output
- 16 KV isolation
- 2Mbit/s
- $t_{PHL}-t_{PLH} \leq 500$ ns
- Creepage path: 0.970" (24.64 mm)
- Air path: 0.970" (24.64 mm)
- UL recognized file No. E58730*



Description:


The **OPI1268** is a high voltage isolator with a digital output that is capable of high speed data transmission. The input of the OPI1268 consists of a high-efficiency GaAlAs LED with a peak wavelength of 850 nm, which is optically coupled to the output optical IC. A photodiode in the output IC detects the incoming modulated light and converts it to a proportionate current. This current is fed into a high-gain linear amplifier which is temperature, current and voltage compensated. The result is a highly stable digital output with an open collector inverter configuration. This device produces DC and AC voltage isolation between the input and output circuitry while providing TTL signal integrity.

Applications:




- Data transmission for High voltage isolation
- PCBoard power system isolation
- Industrial equipment power isolation
- Medical equipment power isolation
- Office equipment

Ordering Information							
Part Number	LED Peak Wavelength	Sensor Photologic®	Isolation Voltage (,000)	t_{PLH} / t_{PHL} Max (ns)	I_F (mA) Typ / Max	V_{CE} (V) Max	Lead Length / Spacing
OPI1268	850 nm	Open Collector	16	100 / 200	10 / 50	18	0.12" / 0.98"

Pin #	Function
1	Cathode
2	Anode
3	Vcc
4	Output
5	Ground



PIN-OUT	
OPI1266	OPI1268
1. ANODE	1. CATHODE
2. CATHODE	2. ANODE
3. Vcc	3. Vcc
4. OUTPUT	4. OUTPUT
5. GROUND	5. GROUND



General Note

TT Electronics reserves the right to make changes in product specification without notice or liability. All information is subject to TT Electronics' own data and is considered accurate at time of going to print.



1645 Wallace Drive, Carrollton, TX 75006 | Ph: +1 972 323 2200
www.optekinc.com | www.ttelectronics.com

High Voltage Isolator

OPI1268

Absolute Maximum Ratings ($T_A = 25^\circ\text{C}$ unless otherwise noted)

Storage Temperature	-40° C to +100° C
Operating Temperature	-40° C to +100° C
Input-to-Output Isolation Voltage ⁽¹⁾⁽²⁾	16 KVDC
Lead Soldering Temperature (1/16" (1.6 mm) from case for 5 seconds with soldering iron) ⁽³⁾	260° C
Input Diode	
Continuous Forward Current	30 mA
Peak Forward current (1 μs pulse width, 300 pps)	3.0 A
Reverse Voltage	3.0 V
Power Dissipation ⁽¹⁾	100 mW
Output IC	
Maximum Supply Voltage	7 V
Power Dissipation ⁽¹⁾	40 mW
Maximum Output Voltage	18 V
Maximum Output Current	25 mA

Electrical Characteristics ($T_A = 0^\circ\text{C}$ to 70°C unless otherwise noted)

SYMBOL	PARAMETER	MIN	TYP	MAX	UNITS	TEST CONDITIONS
Input Diode						
V _F	Forward Voltage	-	1.3	1.6	V	I _F = 20 mA
I _R	Reverse Current	-	0.1	100	μA	V _R = 2.0 V
Output IC (V _{CC} = 4.5 V to 5.25 V) (See OPL550 for additional information—for reference only.)						
I _{OH}	High Level Output Current	-	0.20	10	μA	I _F = 0.0 mA, V _{OH} = 18.0 V, V _{CC} = 5.25 V
V _{OL}	Low Level Output Voltage	-	0.44	0.55	V	I _F = 10.0 mA, I _{OL} = 8.0 mA, V _{CC} = 4.5 V
I _{CCH}	High Level Supply Current	-	4.2	7	mA	I _F = 0, V _{CC} = 5.25V
I _{CCL}	Low Level Supply Current	-	6.7	10		I _F = 10.0 mA, V _{CC} = 5.25 V
Coupled Characteristics (V _{CC} = 5 V)						
C _{IO}	Coupling Capacitance	-	-	2	pF	Input and output leads shorted.
t _{PLH}	Propagation Delay to Low Output Level	-	-	200	ns	See Figure 1
t _{PHL}	Propagation Delay to High Output Level	-	-	100		
I _{ISO}	Isolation Leakage Current	-	-	1	μA	VISO = @ 7kV RMS (input and output leads shorted)
I _{F+}	LED Positive Going Threshold Current	0.8	1.7	5.0	mA	V _{CC} = 5V, I _{OL} = 8.0mA

Notes:







- (1) Derate linearly 1.33 W/°C above 25°C
- (2) UL registered under E58730.
- (3) RMA flux is recommended. The duration can be extended to 10 seconds maximum when flow soldering.

General Note

TT Electronics reserves the right to make changes in product specification without notice or liability. All information is subject to TT Electronics' own data and is considered accurate at time of going to print.

High Voltage Isolator

OPI1268



General Note


TT Electronics reserves the right to make changes in product specification without notice or liability. All information is subject to TT Electronics' own data and is considered accurate at time of going to print.

High Voltage Isolator


OPI1268

dV/dT

OPI1268 dV/dT Emitter



OPI1268 dV/dT Sensor



General Note

TT Electronics reserves the right to make changes in product specification without notice or liability. All information is subject to TT Electronics' own data and is considered accurate at time of going to print.



1645 Wallace Drive, Carrollton, TX 75006 | Ph: +1 972 323 2200
www.optekinc.com | www.ttelectronics.com

AMEYA360

Components Supply Platform

Authorized Distribution Brand :



Website :

Welcome to visit www.ameya360.com

Contact Us :

➤ Address :

401 Building No.5, JiuGe Business Center, Lane 2301, Yishan Rd
Minhang District, Shanghai , China

➤ Sales :

Direct +86 (21) 6401-6692

Email amall@ameya360.com

QQ 800077892

Skype ameyasales1 ameyasales2

➤ Customer Service :

Email service@ameya360.com

➤ Partnership :

Tel +86 (21) 64016692-8333

Email mkt@ameya360.com