



Micro Commercial Components



Micro Commercial Components  
20736 Marilla Street Chatsworth  
CA 91311  
Phone: (818) 701-4933  
Fax: (818) 701-4939

2N4401

## NPN General Purpose Amplifier

### Features

- Lead Free Finish/RoHS Compliant ("P" Suffix designates RoHS Compliant. See ordering information)
- Capable of 625mWatts of Power Dissipation
- Halogen free available upon request by adding suffix "-HF"
- Epoxy meets UL 94 V-0 flammability rating
- Moisture Sensitivity Level 1
- Marking: Type number
- Operating Temperature: -55°C to +150°C
- Storage Temperature: -55°C to +150°C

### Electrical Characteristics @ 25°C Unless Otherwise Specified

| Symbol | Parameter | Min | Max | Units |
|--------|-----------|-----|-----|-------|
|--------|-----------|-----|-----|-------|

#### OFF CHARACTERISTICS

|               |   |     |     |         |
|---------------|---|-----|-----|---------|
| $V_{(BR)CEO}$ | Collector-Emitter Breakdown Voltage*<br>( $I_C=1.0mA$ , $I_B=0$ ) | 40  |     | Vdc     |
| $V_{(BR)CBO}$ | Collector-Base Breakdown Voltage<br>( $I_C=0.1mA$ , $I_E=0$ )     | 60  |     | Vdc     |
| $V_{(BR)EBO}$ | Emitter-Base Breakdown Voltage<br>( $I_E=0.1mA$ , $I_C=0$ )       | 6.0 |     | Vdc     |
| $I_{BL}$      | Base Cutoff Current<br>( $V_{CE}=35Vdc$ , $V_{BE}=0.4Vdc$ )       |     | 0.1 | $\mu A$ |
| $I_{CEX}$     | Collector Cutoff Current<br>( $V_{CE}=35Vdc$ , $V_{BE}=0.4Vdc$ )  |     | 0.1 | $\mu A$ |

#### ON CHARACTERISTICS

|               |  |                             |             |     |
|---------------|--|-----------------------------|-------------|-----|
| $h_{FE}$      | DC Current Gain*<br>( $I_C=0.1mA$ , $V_{CE}=1.0Vdc$ )<br>( $I_C=1.0mA$ , $V_{CE}=1.0Vdc$ )<br>( $I_C=10mA$ , $V_{CE}=1.0Vdc$ )<br>( $I_C=150mA$ , $V_{CE}=1.0Vdc$ )<br>( $I_C=500mA$ , $V_{CE}=1.0Vdc$ ) | 20<br>40<br>80<br>100<br>40 | 300         |     |
| $V_{CE(sat)}$ | Collector-Emitter Saturation Voltage<br>( $I_C=150mA$ , $I_B=15mA$ )<br>( $I_C=500mA$ , $I_B=50mA$ )   |                             | 0.4<br>0.75 | Vdc |
| $V_{BE(sat)}$ | Base-Emitter Saturation Voltage<br>( $I_C=150mA$ , $I_B=15mA$ )<br>( $I_C=500mA$ , $I_B=50mA$ )  | 0.75                        | 0.95<br>1.2 | Vdc |

#### SMALL-SIGNAL CHARACTERISTICS


|          |  |     |      |     |
|----------|--|-----|------|-----|
| $f_T$    | Current Gain-Bandwidth Product<br>( $I_C=20mA$ , $V_{CE}=10Vdc$ , $f=100MHz$ ) | 250 |      | MHz |
| $C_{cb}$ | Collector-Base Capacitance<br>( $V_{CB}=5.0Vdc$ , $I_E=0$ , $f=100kHz$ )       |     | 6.5  | pF  |
| $C_{eb}$ | Emitter-Base Capacitance<br>( $V_{BE}=0.5Vdc$ , $I_C=0$ , $f=100kHz$ )         |     | 30.0 | pF  |

#### SWITCHING CHARACTERISTICS

|       |              |                                      |     |    |
|-------|--------------|--------------------------------------|-----|----|
| $t_d$ | Delay Time   | ( $V_{CC}=30Vdc$ , $V_{BE}=0.2Vdc$ ) | 15  | ns |
| $t_r$ | Rise Time    | ( $I_C=150mA$ , $I_B=15mA$ )         | 20  | ns |
| $t_s$ | Storage Time | ( $V_{CC}=30Vdc$ , $I_C=150mA$ )     | 225 | ns |
| $t_f$ | Fall Time    | ( $I_{B1}=I_{B2}=15mA$ )             | 30  | ns |

\*Pulse Width  $\leq 300\mu s$ , Duty Cycle  $\leq 2.0\%$

### TO-92



STRAIGHT LEAD BULK PACK  
BENT LEAD AMMO PACK







#### DIMENSIONS

| DIM | INCHES |      | MM    |      | NOTE          |
|-----|--------|------|-------|------|---------------|
|     | MIN    | MAX  | MIN   | MAX  |               |
| A   | .175   | .185 | 4.45  | 4.70 |               |
| B   | .175   | .185 | 4.45  | 4.70 |               |
| C   | .500   | ---  | 12.70 | ---  |               |
| D   | .016   | .020 | 0.41  | 0.63 |               |
| E   | .135   | .145 | 3.43  | 3.68 |               |
| G   | .095   | .105 | 2.42  | 2.67 | Straight Lead |
|     | .173   | .220 | 4.40  | 5.60 | Bent Lead     |



\* For ammo packing detailed specification, click here to visit our website of product packaging for details.

[www.mccsemi.com](http://www.mccsemi.com)

# 2N4401



# 2N4401



## Ordering Information :

| Device         | Packing                     |
|----------------|-----------------------------|
| Part Number-AP | Ammo Packing: 20Kpcs/Carton |
| Part Number-BP | Bulk: 100Kpcs/Carton        |

Note : Adding "-HF" suffix for halogen free, eg. Part Number-AP-HF

### \*\*\*IMPORTANT NOTICE\*\*\*

**Micro Commercial Components Corp.** reserves the right to make changes without further notice to any product herein to make corrections, modifications , enhancements , improvements , or other changes . **Micro Commercial Components Corp .** does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights ,nor the rights of others . The user of products in such applications shall assume all risks of such use and will agree to hold **Micro Commercial Components Corp .** and all the companies whose products are represented on our website, harmless against all damages.

### \*\*\*LIFE SUPPORT\*\*\*

MCC's products are not authorized for use as critical components in life support devices or systems without the express written approval of Micro Commercial Components Corporation.

### \*\*\*CUSTOMER AWARENESS\*\*\*

Counterfeiting of semiconductor parts is a growing problem in the industry. Micro Commercial Components (MCC) is taking strong measures to protect ourselves and our customers from the proliferation of counterfeit parts. MCC strongly encourages customers to purchase MCC parts either directly from MCC or from Authorized MCC Distributors who are listed by country on our web page cited below. Products customers buy either from MCC directly or from Authorized MCC Distributors are genuine parts, have full traceability, meet MCC's quality standards for handling and storage. **MCC will not provide any warranty coverage or other assistance for parts bought from Unauthorized Sources.** MCC is committed to combat this global problem and encourage our customers to do their part in stopping this practice by buying direct or from authorized distributors.

# AMEYA360

## Components Supply Platform

Authorized Distribution Brand :



Website :

Welcome to visit [www.ameya360.com](http://www.ameya360.com)

Contact Us :

➤ Address :

401 Building No.5, JiuGe Business Center, Lane 2301, Yishan Rd  
Minhang District, Shanghai , China

➤ Sales :

Direct +86 (21) 6401-6692

Email [amall@ameya360.com](mailto:amall@ameya360.com)

QQ 800077892

Skype ameyasales1 ameyasales2

➤ Customer Service :

Email [service@ameya360.com](mailto:service@ameya360.com)

➤ Partnership :

Tel +86 (21) 64016692-8333

Email [mkt@ameya360.com](mailto:mkt@ameya360.com)