



FEATURES:

- This splice accepts a standard banana plug on one end and a 2.0 (.080) pin tip plug on the other end.

MATERIALS:

Upper Conn.: Banana Jack

Material: Brass per QQ-B-626, Alloy 360, ½ Hard.

Finish: Nickel plated per QQ-N-290, Class 2, 200/300 microinches.

Insulation:

Polypropylene molded to banana jack body and pin tip body.

Marking: "POMONA ELECTRONICS CALIF." "MODEL 3834"

Lower Conn.:

Pin Tip Jack:

Material: Body – Brass per QQ-B-626, Alloy 360, ½ Hard.

Spring – Beryllium copper per QQ-C-533, Alloy 172, Cond. H.T.

Finish: Body – Same as upper conn.

Spring – Gold plated per MIL-G-45204, Type II, Class 00 over electroless nickel per MIL-C-26074, Class 1, 200/300 microinches.

RATINGS:

Operating Temperature: +55°C. (+131°F.) Max.

Operating Voltage: 3000 VDC

Current: 5 Amperes

ORDERING INFORMATION: Model 3834-*

*=Color, -0 Black, -2 Red

Ordering Example: 3834-2 Adapter Color is Red

All dimensions are in inches. Tolerances (except noted): .xx = ±.02" (.51 mm), .xxx = ±.005" (.127 mm).

All specifications are to the latest revisions. Specifications are subject to change without notice.

Registered trademarks are the property of their respective companies. Made in USA

AMEYA360

Components Supply Platform

Authorized Distribution Brand :



Website :

Welcome to visit www.ameya360.com

Contact Us :

➤ Address :

401 Building No.5, JiuGe Business Center, Lane 2301, Yishan Rd
Minhang District, Shanghai , China

➤ Sales :

Direct +86 (21) 6401-6692

Email amall@ameya360.com

QQ 800077892

Skype [ameyasales1](#) [ameyasales2](#)

➤ Customer Service :

Email service@ameya360.com

➤ Partnership :

Tel +86 (21) 64016692-8333

Email mkt@ameya360.com