

.156" x .200"

SERIES 6022/6024

Features

- ☐ Extended card guides
- ☐ Ribbon-type contacts with bifurcated nose
- ☐ Choice of terminations: solder (wire hole and P.C. tab), or low-cost solderless wrap contacts
- ☐ For 1/16" P.C. card

Specifications

Current rating: 5 amperes

Contact resistance: 6 milliohms, maximum

Contact material: Phosphor bronze

Contact plating:*

Overall: 50-100 microinches nickel and 10 microinches min. gold overall

Insertion/withdrawal force: 2 to 16 ounces per contact pair, nominal P.C. card

Insulator material: Polyester per UL 94VO

Insulation resistance: 5000 megohms, minimum

Dielectric withstanding voltage: 1800 VAC between adjacent contacts, RMS, at sea level

Rectangular Tails Series 6007 Contacts

*For other type platings and thicknesses please consult factory.



Ordering Code

Typical Example	00	6022	044	450	001
-----------------	----	------	-----	-----	-----

SERIES

6022

6024



NUMBER OF CONTACTS

6022

6024

Single Readout	Dual Readout
22	44

Single Readout	Dual Readout
18	36

CONTACT CODE

Single Read-Out

552 60-6007-16-33 P.C. tab (single sided): .202" lg.

936 60-6007-06-43 Wrap (.016" x .047") special: .497" lg.

938 60-6007-06-33 P.C. tab special: .215" lg.

940 60-6007-06-23 Wire hole special: .227" lg.

Dual Read-Out

450 60-6007-19-23 Wire hole: .277" lg.

451 60-6007-19-33 P.C. tab: .202" lg.

452 60-6007-18-13 Solderless wrap (.016" x .044"): .697" lg.

453 60-6007-18-23 P.C. tab: .347" lg.

454 60-6007-18-33 Solderless wrap (.016" x .044"): .517" lg.

498 60-6007-05-33 Switching (used in pairs): .202" lg. P.C. tab

941 60-6007-05-13 Switching (used in pairs): .229" lg. wire hole

VARIATION CODE

6022

6024

Plating

Overall

- 001** 44 Dual read-out contacts installed in all positions
- 002** 22 Single read-out contacts installed on numbered side only (551, 552, 936, 938, 940)
- 003** 22 Single read-out contacts installed on lettered side only (551, 552, 936, 938, 940)
- 004** 22 Single read-out contacts installed staggered starting with position 1, B, 3, D, etc. (936, 938, 940 only)
- 005** 22 Single read-out contacts installed staggered starting with position A, 2, C, 4, etc. (936, 938, 940 only)

Plating

Overall

- 001** Dual read-out contacts
- 002** Single read-out contacts with tails in position "1" to "18" (551, 552, 936, 938, 940)
- 003** Single read-out contacts with tails in positions "A" to "V" (551, 552, 936, 938, 940)
- 004** Single read-out contacts with tails in positions 1-B-3, etc. (936, 938, 940 only)
- 005** Single read-out contacts with tails in positions A-2-C, etc. (936, 938, 940 only)

AMEYA360

Components Supply Platform

Authorized Distribution Brand :



Website :

Welcome to visit www.ameya360.com

Contact Us :

➤ Address :

401 Building No.5, JiuGe Business Center, Lane 2301, Yishan Rd
Minhang District, Shanghai , China

➤ Sales :

Direct +86 (21) 6401-6692

Email amall@ameya360.com

QQ 800077892

Skype ameyasales1 ameyasales2

➤ Customer Service :

Email service@ameya360.com

➤ Partnership :

Tel +86 (21) 64016692-8333

Email mkt@ameya360.com