


KSC5338D/KSC5338DW

NPN Triple Diffused Planar Silicon Transistor

Features

- High Voltage Power Switch Switching Application
- Wide Safe Operating Area
- Built-in Free-Wheeling Diode
- Suitable for Electronic Ballast Application
- Small Variance in Storage Time
- Two Package Choices : TO-220 or D²-PAK



Absolute Maximum Ratings $T_a=25^\circ\text{C}$ unless otherwise noted

Symbol	Parameter	Value	Units
V_{CBO}	Collector-Base Voltage	1000	V
V_{CEO}	Collector-Emitter Voltage	450	V
V_{EBO}	Emitter-Base Voltage	12	V
I_C	Collector Current (DC)	5	A
I_{CP}	*Collector Current (Pulse)	10	A
I_B	Base Current (DC)	2	A
I_{BP}	*Base Current (Pulse)	4	A
P_C	Power Dissipation ($T_C=25^\circ\text{C}$)	75	W
T_J	Junction Temperature	150	$^\circ\text{C}$
T_{STG}	Storage Temperature	- 55 to 150	$^\circ\text{C}$

* Pulse Test : Pulse Width = 5ms, Duty Cycle $\leq 10\%$

Thermal Characteristics

Symbol	Parameter		Rating	Units
R _{θjc}	Thermal Resistance	Junction to Case	1.65	°C/W
R _{θja}		Junction to Ambient	62.5	°C/W
T _L	Maximum Lead Temperature for Soldering		270	°C

Electrical Characteristics $T_a=25^\circ\text{C}$ unless otherwise noted

Symbol	Parameter	Test Condition	Min.	Typ.	Max.	Units
BV_{CBO}	Collector-Base Breakdown Voltage	$I_C=1\text{mA}, I_E=0$	1000			V
BV_{CEO}	Collector-Emitter Breakdown Voltage	$I_C=5\text{mA}, I_B=0$	450			V
BV_{EBO}	Emitter-Base Breakdown Voltage	$I_E=1\text{mA}, I_C=0$	12			V
I_{CBO}	Collector Cut-off Current	$V_{CB}=800\text{V}, I_E=0$			10	μA
I_{CES}	Collector Cut-off Current	$V_{CES}=1000\text{V}, I_{EB}=0$	$T_a=25^\circ\text{C}$		100	μA
			$T_a=125^\circ\text{C}$		500	μA
I_{CEO}	Collector Cut-off Current	$V_{CE}=450\text{V}, I_B=0$	$T_a=25^\circ\text{C}$		100	μA
			$T_a=125^\circ\text{C}$		500	μA
I_{EBO}	Emitter Cut-off Current	$V_{EB}=10\text{V}, I_C=0$			10	μA
h_{FE}	DC Current Gain	$V_{CE}=1\text{V}, I_C=0.8\text{A}$	$T_a=25^\circ\text{C}$	15	25	
			$T_a=125^\circ\text{C}$	10	14	
		$V_{CE}=1\text{V}, I_C=2\text{A}$	$T_a=25^\circ\text{C}$	6	9	
			$T_a=125^\circ\text{C}$	4	6	
		$V_{CE}=2.5\text{V}, I_C=1\text{A}$	$T_a=25^\circ\text{C}$	18	25	
			$T_a=125^\circ\text{C}$	14	18	
$V_{CE(sat)}$	Collector-Emitter Saturation Voltage	$I_C=0.8\text{A}, I_B=0.08\text{A}$	$T_a=25^\circ\text{C}$		0.35	0.5 V
			$T_a=125^\circ\text{C}$		0.55	0.75 V
		$I_C=2\text{A}, I_B=0.4\text{A}$	$T_a=25^\circ\text{C}$		0.47	0.75 V
			$T_a=125^\circ\text{C}$		0.9	1.1 V
		$I_C=0.8\text{A}, I_B=0.04\text{A}$	$T_a=25^\circ\text{C}$		0.9	1.5 V
			$T_a=125^\circ\text{C}$		1.8	2.5 V
		$I_C=1\text{A}, I_B=0.2\text{A}$	$T_a=25^\circ\text{C}$		0.22	0.5 V
			$T_a=125^\circ\text{C}$		0.3	0.6 V
$V_{BE(sat)}$	Base-Emitter Saturation Voltage	$I_C=0.8\text{A}, I_B=0.08\text{A}$	$T_a=25^\circ\text{C}$		0.8	1.0 V
			$T_a=125^\circ\text{C}$		0.65	0.9 V
		$I_C=2\text{A}, I_B=0.4\text{A}$	$T_a=25^\circ\text{C}$		0.9	1.0 V
			$T_a=125^\circ\text{C}$		0.8	0.9 V
C_{ib}	Input Capacitance	$V_{EB}=10\text{V}, I_C=0.5\text{A}, f=1\text{MHz}$		550	750	pF
C_{ob}	Output Capacitance	$V_{CB}=10\text{V}, I_E=0, f=1\text{MHz}$		60	100	pF
f_T	Current Gain Bandwidth Product	$I_C=0.5\text{A}, V_{CE}=10\text{V}$		11		MHz
V_F	Diode Forward Voltage	$I_F=1\text{A}, I_C=1\text{mA}, I_E=0$	$T_a=25^\circ\text{C}$		0.86	1.3 V
			$T_a=125^\circ\text{C}$		0.79	V
		$I_F=2\text{A}$	$T_a=25^\circ\text{C}$		0.95	1.5 V
			$T_a=125^\circ\text{C}$		0.88	V
t_{fr}	Diode Forward Recovery Time ($di/dt=10\text{A}/\mu\text{s}$)	$I_F=0.4\text{A}$		460		ns
		$I_F=1\text{A}$		360		ns
		$I_F=2\text{A}$		325		ns
$V_{CE(DSAT)}$	Dynamic Saturation Voltage	$I_C=1\text{A}, I_{B1}=100\text{mA}$ $V_{CC}=300\text{V}$ at 1 μs	$T_a=25^\circ\text{C}$		8	V
			$T_a=125^\circ\text{C}$		15	V
		$I_C=1\text{A}, I_{B1}=100\text{mA}$ $V_{CC}=300\text{V}$ at 3 μs	$T_a=25^\circ\text{C}$		2.9	V
			$T_a=125^\circ\text{C}$		8	V
		$I_C=2\text{A}, I_{B1}=400\text{mA}$ $V_{CC}=300\text{V}$ at 1 μs	$T_a=25^\circ\text{C}$		9	V
			$T_a=125^\circ\text{C}$		17	V
		$I_C=2\text{A}, I_{B1}=400\text{mA}$ $V_{CC}=300\text{V}$ at 3 μs	$T_a=25^\circ\text{C}$		1.9	V
			$T_a=125^\circ\text{C}$		8.5	V

Electrical Characteristics (Continued) $T_a=25^\circ\text{C}$ unless otherwise noted

Symbol	Parameter	Test Condition		Min	Typ.	Max.	Units
RESISTIVE LOAD SWITCHING (D.C ≤ 10%, Pulse Width=40μs)							
t _{ON}	Turn On Time	I _C =2.5A, I _{B1} =500mA, I _{B2} =-1A, V _{CC} =250V, R _L = 100Ω		1.2	500	750	ns
t _{STG}	Storage Time				1.5	μs	
t _F	Fall Time				100	200	ns
t _{ON}	Turn On Time	I _C =2A, I _{B1} =400mA, I _{B2} =-1A, V _{CC} =300V, R _L = 150Ω	T _a =25°C		100	150	ns
			T _a =125°C		150		ns
t _{STG}	Storage Time		T _a =25°C		1.4	2.2	μs
			T _a =125°C		1.7		μs
t _F	Fall Time		T _a =25°C		90	150	ns
			T _a =125°C		150		ns
t _{ON}	Turn On Time	I _C =2.5A, I _{B1} =500mA, I _{B2} =-5mA, V _{CC} =300V, R _L = 120Ω	T _a =25°C		120	150	ns
			T _a =125°C		150		ns
t _{STG}	Storage Time		T _a =25°C	1.8		2.1	μs
			T _a =125°C		2.6		μs
t _F	Fall Time		T _a =25°C		110	150	ns
			T _a =125°C		160		ns
INDUCTIVE LOAD SWITCHING (V _{CC} =15V)							
t _{STG}	Storage Time	I _C =2.5A, I _{B1} =500mA, I _{B2} =-0.5A, V _Z =350V, L _C =300μH	T _a =25°C		1.9	2.2	μs
			T _a =125°C		2.4		μs
t _F	Fall Time		T _a =25°C		160	200	ns
			T _a =125°C		330		ns
t _C	Cross-over Time	I _C =2A, I _{B1} =400mA, I _{B2} =-0.4A, V _Z =300V, L _C =200μH	T _a =25°C		350	500	ns
			T _a =125°C		750		ns
t _{STG}	Storage Time		T _a =25°C	1.95		2.25	μs
			T _a =125°C		2.9		μs
t _F	Fall Time	I _C =2A, I _{B1} =400mA, I _{B2} =-0.4A, V _Z =300V, L _C =200μH	T _a =25°C		120	150	ns
			T _a =125°C		270		ns
t _C	Cross-over Time		T _a =25°C		300	450	ns
			T _a =125°C		700		ns
t _{STG}	Storage Time	I _C =1A, I _{B1} =100mA, I _{B2} =-0.5A, V _Z =300V, L _C =200μH	T _a =25°C		0.6	0.8	μs
			T _a =125°C		1.0		μs
t _F	Fall Time		T _a =25°C		70		ns
			T _a =125°C		110		ns
t _C	Cross-over Time	I _C =1A, I _{B1} =100mA, I _{B2} =-0.5A, V _Z =300V, L _C =200μH	T _a =25°C		80	130	ns
			T _a =125°C		170		ns

Typical Characteristics




Figure 1. Static Characteristic




Figure 2. DC current Gain




Figure 3. DC current Gain




Figure 4. Collector-Emitter Saturation Voltage




Figure 5. Collector-Emitter Saturation Voltage




Figure 6. Base-Emitter Saturation Voltage

Typical Characteristics (Continued)




Figure 7. Base-Emitter Saturation Voltage




Figure 8. Collector Output Capacitance




Figure 9. Forward Recovery Time




Figure 10. Switching Time




Figure 11. Induction Storage Time




Figure 12. Inductive Crossover Time

Typical Characteristics (Continued)




Figure 13. Inductive Fall Time




Figure 14. Safe Operating Area




Figure 15. Reverse Bias Safe Operating




Figure 16. Power Derating





Figure 17. RBSOA Saturation

Physical Dimensions

TO-220



Dimensions in Millimeters



TRADEMARKS

The following includes registered and unregistered trademarks and service marks, owned by Fairchild Semiconductor and/or its global subsidiaries, and is not intended to be an exhaustive list of all such trademarks.

AccuPower™	F-PFS™	Power-SPM™	SYSTEM®*
Auto-SPM™	FRFET®	PowerTrench®	GENERAL
Build it Now™	Global Power Resource™	PowerXS™	The Power Franchise®
CorePLUS™	Green FPS™	Programmable Active Droop™	the
CorePOWER™	Green FPS™ e-Series™	QFET®	power®
CROSSVOLT™	Gmax™	QS™	franchise
CTL™	GTO™	Quiet Series™	TinyBoost™
Current Transfer Logic™	IntelliMAX™	RapidConfigure™	TinyBuck™
DEUXPEED®	ISOPLANAR™	TM	TinyCalc™
Dual Cool™	MegaBuck™	TM	TinyLogic®
EcoSPARK®	MICROCOUPLER™	TM	TINYOPTO™
EfficientMax™	MicroFET™	TM	TinyPower™
ESBC™	MicroPak™	TM	TinyPWM™
F®	MicroPak2™	TM	TinyWire™
Fairchild®	MillerDrive™	TM	TriFault Detect™
Fairchild Semiconductor®	MotionMax™	TM	TRUECURRENT™*
FACT Quiet Series™	Motion-SPM™	TM	µSerDes™
FACT®	OptoHiT™	TM	TM
FAST®	OPTOLOGIC®	TM	SerDes®
FastvCore™	OPTOPLANAR®	TM	UHC®
FETBench™	®	TM	Ultra FRFET™
FlashWriter®*	PDP SPM™	TM	UniFET™
FPS™		TM	VCX™
		TM	VisualMax™
		TM	XS™

* Trademarks of System General Corporation, used under license by Fairchild Semiconductor.

DISCLAIMER

FAIRCHILD SEMICONDUCTOR RESERVES THE RIGHT TO MAKE CHANGES WITHOUT FURTHER NOTICE TO ANY PRODUCTS HEREIN TO IMPROVE RELIABILITY, FUNCTION, OR DESIGN. FAIRCHILD DOES NOT ASSUME ANY LIABILITY ARISING OUT OF THE APPLICATION OR USE OF ANY PRODUCT OR CIRCUIT DESCRIBED HEREIN; NEITHER DOES IT CONVEY ANY LICENSE UNDER ITS PATENT RIGHTS, NOR THE RIGHTS OF OTHERS. THESE SPECIFICATIONS DO NOT EXPAND THE TERMS OF FAIRCHILD'S WORLDWIDE TERMS AND CONDITIONS, SPECIFICALLY THE WARRANTY THEREIN, WHICH COVERS THESE PRODUCTS.

LIFE SUPPORT POLICY

FAIRCHILD'S PRODUCTS ARE NOT AUTHORIZED FOR USE AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS WITHOUT THE EXPRESS WRITTEN APPROVAL OF FAIRCHILD SEMICONDUCTOR CORPORATION.

As used herein:

1. Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body or (b) support or sustain life, and (c) whose failure to perform when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in a significant injury of the user.
2. A critical component in any component of a life support, device, or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.

ANTI-COUNTERFEITING POLICY

Fairchild Semiconductor Corporation's Anti-Counterfeiting Policy. Fairchild's Anti-Counterfeiting Policy is also stated on our external website, www.fairchildsemi.com, under Sales Support.

Counterfeiting of semiconductor parts is a growing problem in the industry. All manufacturers of semiconductor products are experiencing counterfeiting of their parts. Customers who inadvertently purchase counterfeit parts experience many problems such as loss of brand reputation, substandard performance, failed applications, and increased cost of production and manufacturing delays. Fairchild is taking strong measures to protect ourselves and our customers from the proliferation of counterfeit parts. Fairchild strongly encourages customers to purchase Fairchild parts either directly from Fairchild or from Authorized Fairchild Distributors who are listed by country on our web page cited above. Products customers buy either from Fairchild directly or from Authorized Fairchild Distributors are genuine parts, have full traceability, meet Fairchild's quality standards for handling and storage and provide access to Fairchild's full range of up-to-date technical and product information. Fairchild and our Authorized Distributors will stand behind all warranties and will appropriately address any warranty issues that may arise. Fairchild will not provide any warranty coverage or other assistance for parts bought from Unauthorized Sources. Fairchild is committed to combat this global problem and encourage our customers to do their part in stopping this practice by buying direct or from authorized distributors.

PRODUCT STATUS DEFINITIONS

Definition of Terms

Datasheet Identification	Product Status	Definition
Advance Information	Formative / In Design	Datasheet contains the design specifications for product development. Specifications may change in any manner without notice.
Preliminary	First Production	Datasheet contains preliminary data; supplementary data will be published at a later date. Fairchild Semiconductor reserves the right to make changes at any time without notice to improve design.
No Identification Needed	Full Production	Datasheet contains final specifications. Fairchild Semiconductor reserves the right to make changes at any time without notice to improve the design.
Obsolete	Not In Production	Datasheet contains specifications on a product that is discontinued by Fairchild Semiconductor. The datasheet is for reference information only.

Rev. I49

AMEYA360

Components Supply Platform

Authorized Distribution Brand :



Website :

Welcome to visit www.ameya360.com

Contact Us :

➤ Address :

401 Building No.5, JiuGe Business Center, Lane 2301, Yishan Rd
Minhang District, Shanghai , China

➤ Sales :

Direct +86 (21) 6401-6692

Email amall@ameya360.com

QQ 800077892

Skype ameyasales1 ameyasales2

➤ Customer Service :

Email service@ameya360.com

➤ Partnership :

Tel +86 (21) 64016692-8333

Email mkt@ameya360.com