

7.0" Capacitive Touch Screen LCD GUI





The uEZ GUI® provides everything you need right out of the box to have a touch screen GUI instantly in your project.

Each uEZ GUI unit is available in two convenient forms. To get your project started quickly we offer a full development kit complete with JTAG debugger, power supply, cables, a microSD card and full documentation. The Dev Kit Part Number is **uEZGUI-1788-70WVM**. Once your design is complete, we also offer a cost-effective production module for prototypes or even for high volume production. The module includes the touchscreen display, all of the necessary hardware, and is supported by the uEZ® / FreeRTOS™ open source software. The uEZ GUI module is available off-the-shelf from any of our franchised distributors under Part Number uEZGUI-1788-70WVM-BA.

Features

• 7.0" TFT WVGA 800x480 LCD Panel with Projected Capacitive Touch Screen

- NXP LPC1788 120MHz CPU with 512KB Internal Flash
- 8MB of SDRAM, 16MB on Rev 2.0 and later (optional to 32MB)
- 8MB of NOR FLASH (optional to 16MB)
- High Speed SD interface supporting 15 fps video playback
- 4GB microSD Memory Card
- USB Device Mini-AB PC communications
- USB Device Mini-B connector for 5.0VDC power
- NV Data Storage via 4KB Internal EEPROM
- Internal Real-Time Clock with Supercap Backup
- Speaker, 3-axis Accelerometer, Temperature Sensor
- Mini-JTAG Debug Connector
- Optional 802.11n Wi-Fi module
- External Expansion via two I/O connectors (70 pins) -UART, I2C, SPI, USB Host/Device, RMII Ethernet







Rowley Associates











Module <\$220 in volume!

partner of

Module Specifications

- Module P/N: uEZGUI-1788-70WVM-BA
- Contrast Ratio: 1000 typical
- Luminance: 400 cd/m2 typical
- Viewing Angle Horizontal: 85° L / 85° R
- Viewing Angle Vertical: 85° U /85° D
- Power consumption typ/max: 750/1250mA @ 5.0VDC
- Operating Temperature Range: -20°C to +70°C
- Overall Size: 6.70"W x 5.20"H x 0.70"T
- Viewable area: 6.0"W x 3.60"H
- Weight: 270g
- Touch Resolution: 800x480
- Number Simultaneous Touches:1
- Glass Overlay: ITO Glass T = 0.7mm

μΕΖ**°** OSAL

FreeRTOS™

Glass Hardness: ≥ 7H

The uEZGUI-1788-70WVM-BA is the stand alone System On Module version and is priced at less than \$220.00 in volume. This unit is designed to be used as an "off-the-shelf" Graphical User Interface (GUI) or Human Machine Interface (HMI) in a variety of end customer applications. The miniature, self-contained design is well suited to embed directly into your product or FDI offers prepackaged versions. FDI also offers low cost customization services for customer specific hardware, software or packaging applications at volumes of 500 units or more.

Software

μΕΖ® (pronounced Muse) is an open source rapid development platform that supplies application developers with an extensive library of open source software, drivers, and processor support all under a common framework. µEZ® allows companies to focus on innovation and their value-added applications while minimizing development time and maximizing software reuse.

The diagram to the right shows a typical embedded application stack. The µEZ® components comprise three primary categories to simplify embedded application development:

- Operating System Abstraction Layer (μΕΖ® OSAL)
- Sub-system drivers (ex: μΕΖ® TCP/IP, μΕΖ® USB, μΕΖ® Driver)
- Hardware Abstraction Layer (µEZ® HAL)

Software Included:

- Customized versions available

uEZ® / FreeRTOS Rapid Development Platform uEZ® / SafeRTOS option for Medical/Safety Apps MicroSD card maps as USB Flash Drive to the PC • Rowley CrossWorks Compiler and Tool Suite Segger J-Link Lite JTAG for programming and debug

Ordering Information

Kit Part Number: uEZGUI-1788-70WVM Suggested Resale Price: \$475.00(USD) Order Online at: www.uEZGUI.com or from any

of our franchised distributors

Warranty: 30-day money back guarantee Phone 256-883-1240 Fax 256-883-1241

sales@teamfdi.com

Kit Contents:

- uEZGUI-1788-70WVM-BA Production Module
- · USB Device cables for Power and PC communications

Kit Contents

- AC Power Supply
- Mini JTAG Debugger with cables
- MicroSD Card

Download Users Manual, documents, schematics, and software examples at: www.uEZGUI.com





www.teamfdi.com (256)883-1240





Applications

Embedded Microprocessor

Device OTG

μΕΖ® HAL

Hardware Peripheral API

AMEYA360 Components Supply Platform

Authorized Distribution Brand:

























Website:

Welcome to visit www.ameya360.com

Contact Us:

Address:

401 Building No.5, JiuGe Business Center, Lane 2301, Yishan Rd Minhang District, Shanghai , China

> Sales:

Direct +86 (21) 6401-6692

Email amall@ameya360.com

QQ 800077892

Skype ameyasales1 ameyasales2

Customer Service :

Email service@ameya360.com

Partnership :

Tel +86 (21) 64016692-8333

Email mkt@ameya360.com