



NGTG20N60L2TF1G

N-Channel IGBT

600V, 20A, $V_{CE(sat)}$;1.45V Single TO-3PF-3L

ON Semiconductor®

<http://onsemi.com>

Features

- IGBT $V_{CE(sat)}$ =1.45V typ. (I_C =20A, V_{GE} =15V)
- IGBT t_f =67ns typ.
- Enhancement type
- Adaption of full isolation type package
- Maximum junction temperature T_j =175°C

Applications

- Power factor correction of white goods appliance
- General purpose inverter

Specifications

Absolute Maximum Ratings at $T_a = 25^\circ\text{C}$, Unless otherwise specified

Parameter	Symbol	Conditions	Ratings	Unit	
Collector to Emitter Voltage	V_{CES}		600	V	
Gate to Emitter Voltage	V_{GES}		± 20	V	
Collector Current (DC)	I_C *1	Limited by T_{jmax}	@ $T_c=25^\circ\text{C}$ *2	40	A
			@ $T_c=100^\circ\text{C}$ *2	20	A
Collector Current (Pulse)	I_{CP}	Pulse width Limited by T_{jmax}	105	A	
Allowable Power Dissipation	P_D	$T_c=25^\circ\text{C}$ (Our ideal heat dissipation condition) *2	64	W	
Junction Temperature	T_j		175	°C	
Storage Temperature	T_{stg}		-55 to +175	°C	

Note : *1 Collector Current is calculated from the following formula.

$$I_C(T_c) = \frac{T_{jmax} - T_c}{R_{th(j-c)} \times V_{CE(sat)}(T_j, I_C(T_c))}$$


*2 Our condition is radiation from backside.

The method is applying silicone grease to the backside of the device and attaching the device to water-cooled radiator made of aluminium.

Stresses exceeding Maximum Ratings may damage the device. Maximum Ratings are stress ratings only. Functional operation above the Recommended Operating Conditions is not implied. Extended exposure to stresses above the Recommended Operating Conditions may affect device reliability.

Package Dimensions


unit : mm (typ) 7538-001




Ordering & Package Information

Device	Package	Shipping	note
NGTG20N60L2TF1G	TO-3PF-3L SC-94	30 pcs. / tube	Pb-Free

Marking



Electrical Connection



NGTG20N60L2TF1G

Electrical Characteristics at Ta = 25°C, Unless otherwise specified

Parameter	Symbol	Conditions	Ratings			Unit
			min	typ	max	
Collector to Emitter Breakdown Voltage	$V_{(BR)CES}$	$I_C=500\mu A, V_{GE}=0V$	600			V
Collector to Emitter Cut off Current	I_{CES}	$V_{CE}=600V, V_{GE}=0V$	$T_c=25^\circ C$		10	μA
			$T_c=150^\circ C$		1	mA
Gate to Emitter Leakage Current	I_{GES}	$V_{GE}=\pm 20V, V_{CE}=0V$			± 100	nA
Gate to Emitter Threshold Voltage	$V_{GE(th)}$	$V_{CE}=20V, I_C=250\mu A$	4.5		6.5	V
Collector to Emitter Saturation Voltage	$V_{CE(sat)}$	$V_{GE}=15V, I_C=20A$	$T_c=25^\circ C$	1.45	1.65	V
			$T_c=150^\circ C$	1.8		V
Input Capacitance	C_{ies}	$V_{CE}=20V, f=1MHz$		2000		pF
Output Capacitance	C_{oes}			60		pF
Reverse Transfer Capacitance	C_{res}			50		pF
Turn-ON Delay Time	$t_{d(on)}$			60		ns
Rise Time	t_r	$V_{CC}=300V, I_C=20A$ $R_G=30\Omega, L=200\mu H$ $V_{GE}=0V/15V$ $V_{clamp}=400V$ See Fig.1, See Fig.2		37		ns
Turn-ON Time	t_{on}			400		ns
Turn-OFF Delay Time	$t_{d(off)}$			193		ns
Fall Time	t_f			67		ns
Turn-OFF Time	t_{off}			281		ns
Total Gate Charge	Q_g	$V_{CE}=300V, V_{GE}=15V, I_C=20A$		84		nC
Gate to Emitter Charge	Q_{ge}			16		nC
Gate to Collector "Miller" Charge	Q_{gc}			37		nC

Thermal Characteristics at Ta = 25°C, Unless otherwise specified

Parameter	Symbol	Conditions	Ratings	Unit
Thermal Resistance (junction- Case)	$R_{th(j-c)}$	$T_c=25^\circ C$ (our ideal heat dissipation condition)*2	2.33	$^\circ C/W$
Thermal Resistance (junction- atmosphere)	$R_{th(j-a)}$		47.5	$^\circ C/W$

Fig.1 Switching Time Test Circuit













Fig.2 Timing Chart










IT16383

NGTG20N60L2TF1G




NGTG20N60L2TF1G




NGTG20N60L2TF1G


Forward Bias A S O




Reverse Bias A S O



$P_D - T_c$




$I_C - T_c$



NGTG20N60L2TF1G

Outline Drawing

NGTG20N60L2TF1G



ON Semiconductor and the ON logo are registered trademarks of Semiconductor Components Industries, LLC (SCILLC). SCILLC owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of SCILLC's product/patent coverage may be accessed at www.onsemi.com/site/pdf/Patent-Marking.pdf. SCILLC reserves the right to make changes without further notice to any products herein. SCILLC makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does SCILLC assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. "Typical" parameters which may be provided in SCILLC data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. SCILLC does not convey any license under its patent rights nor the rights of others. SCILLC products are not designed, intended, or authorized for use as components in systems intended for surgical implant into the body, or other applications intended to support or sustain life, or for any other application in which the failure of the SCILLC product could create a situation where personal injury or death may occur. Should Buyer purchase or use SCILLC products for any such unintended or unauthorized application, Buyer shall indemnify and hold SCILLC and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that SCILLC was negligent regarding the design or manufacture of the part. SCILLC is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

AMEYA360

Components Supply Platform

Authorized Distribution Brand :



Website :

Welcome to visit www.ameya360.com

Contact Us :

➤ Address :

401 Building No.5, JiuGe Business Center, Lane 2301, Yishan Rd
Minhang District, Shanghai , China

➤ Sales :

Direct +86 (21) 6401-6692

Email amall@ameya360.com

QQ 800077892

Skype [ameyasales1](#) [ameyasales2](#)

➤ Customer Service :

Email service@ameya360.com

➤ Partnership :

Tel +86 (21) 64016692-8333

Email mkt@ameya360.com