

HDMI^(TM): KDMIX-SL1 Series

SLIM UPRIGHT Type A Through Hole Shield No Flange With Spring HDMI^(TM)

Product Features

Metal Shields Provide Better ESD Protection
19 Position Receptacle
Saves Board Space

Performance Specifications

Materials and Finish

Housing Material

High Temperature Thermoplastic, UL94V-0 Rated,
Color Black

Contacts

Brass

Plating

15μ" Gold Plated over Nickel in Contact Area,
Tin Plated in Solder Area.

Electrical Characteristics

Rated Current

0.5A

Insulation Resistance

More than 100 Megohms at 500V DC

Dielectric Withstanding

500V for 1 Minute

Mechanical Characteristics

Durability

10000 Mating Cycles Min.

Operating Temperature

-40°C to +105°C

2D Drawing	IGES	STEP	3D PDF
Solder Profile	CofC RoHS Compliant	CofC REACH Compliant	UL Plastic File
Certificate of Origin	Check Stock	Request a Sample	Send Us An Email

Generated Part Number

Part Number Builder

	-				
Series		Shield Option	Top Spring	Insulator Option	Plating Option

Series

KDMIX-SL1 - HDMI^(TM) Slim

Shield Option

NS - Through Hole Shield Tabs

Top Spring

WS - With Top Spring

Insulator Option

B - Black



Plating Option

15 - 15μ" Gold



Contact Kycon for Other Options

KDMIX-SL1

Dimensions in mm



Reference Panel Cut Out Dimension



AMEYA360

Components Supply Platform

Authorized Distribution Brand :



Website :

Welcome to visit www.ameya360.com

Contact Us :

➤ Address :

401 Building No.5, JiuGe Business Center, Lane 2301, Yishan Rd
Minhang District, Shanghai , China

➤ Sales :

Direct +86 (21) 6401-6692
Email amall@ameya360.com
QQ 800077892
Skype ameyasales1 ameyasales2

➤ Customer Service :

Email service@ameya360.com

➤ Partnership :

Tel +86 (21) 64016692-8333
Email mkt@ameya360.com