






OPTIONAL TERMINALS
FOR PUSH ON OR
SOLDER CONNECTIONS
(.032 X .250) [0.8 X 6.4]




(4) STANDOFFS TAPPED
1/4-28 X .38 [9.5] DEEP
FOR MOUNTING BOLTS

- + MOTOR DRIVEN UNITS USE TERMINAL CONNECTIONS FOR CCW INCREASING VOLTAGE, AS VIEWED FROM BASE END.
- π IF GANGED UNITS ARE USED IN A SYSTEM THAT ORDINARILY HAS A COMMON NEUTRAL OR GROUND BETWEEN SOURCE AND LOAD, THE NEUTRAL OR GROUND MUST BE CONNECTED TO THE COMMON TERMINALS OF THE VARIABLE TRANSFORMER ASSEMBLY. IF THE SYSTEM HAS NO NEUTRAL, THE LOAD MUST BE BALANCED OR THE TRANSFORMER WILL BE DAMAGED.
- JUMPER PROVIDED IN STANDARD COMMON POSITION AND SHOULD BE MOVED OR REMOVED AS REQUIRED.
- ++ LINE TO LINE VOLTAGE.



SCHEMATIC

(FUSE RECOMMENDED BUT NOT SUPPLIED)



MOTOR CIRCUIT
120V, 50/60 HZ
* ROTATION AS VIEWED
FROM MOTOR END
MOTOR SPEED: SEE CHART

SPEED (SECONDS)	MODEL NUMBER	DIM "A"
5	5M1010B-2	15.40 [391.2]
15	15M1010B-2	15.40 [391.2]
30	30M1010B-2	15.79 [401.1]
60	60M1010B-2	15.79 [401.1]

SPECIFICATIONS															
WIRING	INPUT		VOLTS	OUTPUT				SHAFT ROTATION TO INCREASE VOLTAGE	TERMINAL CONNECTIONS						
	VOLTS	HERTZ		CONSTANT CURRENT LOAD		CONSTANT IMPEDANCE LOAD			FOR INCREASING VOLTAGE AS VIEWED FROM BASE END +						
			MAX. AMPS	MAX. KVA	MAX. AMPS	MAX. KVA	INPUT		JUMPER ■	OUTPUT					
	SINGLE PHASE SERIES	240	50/60	0-240	10	2.4	13	3.12	CW	1-1	4-4	3-3			
									CCW	4-4	1-1	3-3			
0-280				10	2.8	—	—	CW	5-5	4-4	3-3				
									CCW	2-2	1-1	3-3			
THREE PHASE OPEN DELTA π	120 ++	50/60	0-120	10	2.08	13	2.70	CW	1-4-1	4-4	3-4-3				
									CCW	4-1-4	1-1	3-1-3			
			0-140	10	2.42	—	—	CW	5-4-5	4-4	3-4-3				
									CCW	2-1-2	1-1	3-1-3			
UNLESS OTHERWISE SPECIFIED, TOLERANCE IS ± DECIMALS .XX .005 HOLES .002 ANGLES 1° DRAFT 1-1/2°				UNITS IN [mm]		TITLE: SPEC. CONTROL DRAWING MOTORIZED VARIABLE XFMR MODEL: M1010B-2			 STACO ENERGY PRODUCTS CO. A COMPONENTS CORPORATION OF AMERICA COMPANY DAYTON, OHIO U.S.A.						
MATERIAL		ALL DIMENSIONS APPLY AFTER PLATING													
The information and design disclosed herein was originated by and is the property of STACO ENERGY PRODUCTS CO., which reserves all patent, proprietary, design, manufacturing, reproduction, use and sale rights thereto, and to any article disclosed therein except to the extent rights are expressly granted to others. The foregoing does not apply to vendor proprietary parts.				DRAWN BY S.A. SMITH		DATE 9/19/97		FIRST USED ON		DO NOT SCALE DWG.		CUSTOMER APPROVAL		DATE	
				CHECKER		DATE		WEIGHT APPROX. 29 LBS		CODE IDENT. NO. 83008		DWG. SIZE		DWG. NO.	
				ENGINEER		DATE		SCALE 1 = 1		SHEET 1 OF 1		D		031-1740	



Authorized Distribution Brand :



Website :

Welcome to visit www.ameya360.com

Contact Us :

➤ Address :

401 Building No.5, JiuGe Business Center, Lane 2301, Yishan Rd
Minhang District, Shanghai , China

➤ Sales :

Direct +86 (21) 6401-6692

Email amall@ameya360.com

QQ 800077892

Skype ameyasales1 ameyasales2

➤ Customer Service :

Email service@ameya360.com

➤ Partnership :

Tel +86 (21) 64016692-8333

Email mkt@ameya360.com