


MATERIALS:

	CENTER CONTACT	DIELECTRIC	SHELL
1- TYPE `N` MALE	Gold Plated Phosphor Bronze	Teflon	Silver Plated Brass
2- BNC MALE	Gold Plated Phosphor Bronze	Teflon	Silver Plated Brass
3- TNC MALE	Gold Plated Phosphor Bronze	Teflon	Silver Plated Brass
4- SMA MALE	Gold Plated Phosphor Bronze	Teflon	Silver Plated Brass
5- TYPE `N` FEMALE	Gold Plated Phosphor Bronze	Teflon	Silver Plated Brass
6- BNC FEMALE	Gold Plated Phosphor Bronze	Teflon	Silver Plated Brass
7- TNC FEMALE	Gold Plated Phosphor Bronze	Teflon	Silver Plated Brass
8- SMA FEMALE	Gold Plated Phosphor Bronze	Teflon	Silver Plated Brass
9- COUPLING NUT	Gold Plated Phosphor Bronze	Teflon	Silver Plated Brass

All dimensions are in inches. Tolerances (except noted): .xx = ±.02" (.51 mm), .xxx = ±.005" (.127 mm).
 All specifications are to the latest revisions. Specifications are subject to change without notice.
 Registered trademarks are the property of their respective companies. Made in USA


10- DOUBLE BANANA PLUG



SCHEMATIC

Spring: Beryllium copper ASTM B194, alloy 172 cond. Ht.
 Plug Body: Brass per QQ-B-626, alloy 360, ½ hard.
 Finish: Nickel plated per QQ-N-290, class2, 200/300 microinches
 Insulation: ABS. Color: Black. Marking: Pomona Electronics, Center
 Contact: Gold plated brass
 Dielectric: Teflon Shell: Silver plated brass

11- DOUBLE BINDING POST



SCHEMATIC

Body: Brass per QQ-B-626, alloy 360, ½ hard
 Finish: Nickel plated per QQ-N-290, class 2, 200/300 microinches
 Insulation: Polycarbonate. Color: one black, one red
 Insulation, Body: ABS. Color: Black
 Center Contact: Gold plated phosphor bronz
 Dielectric: Teflon
 Shell: Silver plated brass

	CENTER CONTACT	DIELECTRIC	SHELL
21- LABEL, NOT SHOWN			
22- PLASTIC BOX W/ FOAMS			
23- PART CARD, NOT SHOWN			

RATINGS:

Operating Temperature:

Items 1 through 9 and 12 through 20 : -67° F to +302° F (55° C to +150° C).

Items 10 and 11 : +122° F. (+50° C.) Max.

Nomial Impedance:

Items 1 through 9 and 20: 50 Ohms.

Vswr Max.: Items 1-9 is 1.2:1 (DC-1GHz)

Frequency Range: 1-9 1GHz Max.

All dimensions are in inches. Tolerances (except noted): .xx = ±.02" (.51 mm), .xxx = ± .005" (.127 mm).

All specifications are to the latest revisions. Specifications are subject to change without notice.

Registered trademarks are the property of their respective companies. Made in USA

AMEYA360

Components Supply Platform

Authorized Distribution Brand :



Website :

Welcome to visit www.ameya360.com

Contact Us :

➤ Address :

401 Building No.5, JiuGe Business Center, Lane 2301, Yishan Rd
Minhang District, Shanghai , China

➤ Sales :

Direct +86 (21) 6401-6692

Email amall@ameya360.com

QQ 800077892

Skype [ameyasales1](#) [ameyasales2](#)

➤ Customer Service :

Email service@ameya360.com

➤ Partnership :

Tel +86 (21) 64016692-8333

Email mkt@ameya360.com