



Heyco® -Tite UL Listed/Recognized and CSA Certified Liquid Tight Cordgrips for Solar Applications

Multi-Hole, NPT Hubs with Integral Sealing Ring - IP 68 Rated

The Ultimate in Liquid Tight Strain Relief Protection

- Integral Sealing Ring ensures a superior seal at the clearance or threaded mounting hole location, every time.
- IP 68 rated.
- Widest range of approved cable diameters.
- Cordgrips with an -SM suffix have Skinned-Over Break-thru glands that offer the flexibility to use from 1 to 31 of the available holes while still providing a liquid tight seal around the wire.
- All accompanying Cordgrips are made of nylon construction with TPE sealing glands that resist salt water, weak acids, gasoline, alcohol, oil, grease, and common solvents. (This feature is not assessed by UL.)
- For locknut specifications or to order locknuts separately, see pages 3-39 & 3-40.
- Multi-hole glands are only to be used with Heyco Liquid Tight Cordgrips and are not sold separately.
- For our complete range of Heyco Cordgrips, see Section 3.

GLAND CONFIGURATION			PART NUMBER Black	DESCRIPTION	UL/CSA or SR	PART DIMENSIONS									
Size mm.	Type *	No.				A Clearance Hole Dia. in. mm.	B Max. O.A. Length in. mm.	C Thread Length in. mm.	D Thickness in. mm.		E Wrenching Nut Flat Size in. mm.				

Standard Multi-Hole Gland - Assembled Metal Locknuts INCLUDED															
4,5	USE-2	9	M8437GBF	LTCG 1	UL/CSA	1.33	33,8	2.41	61,2	.76	19,3	.30	7,6	1.73	43,9
		13	M4524GBG	LTCG 1-1/4		1.68	42,7	2.69	68,3	.78	19,8	.30	7,6	2.05	52,1
5,2	USE-2	2	M3231GAE	LTCG 1/2	UL/CSA	.87	22,2	1.70	43,2	.61	15,5	.21	5,3	.98	24,9
		3	M3234GAF	LTCG 3/4	UL/CSA	1.04	26,4	2.00	50,8	.62	15,7	.25	6,4	1.30	33,0
4	M3234GAG	UL/CSA	1.04		26,4	2.00	50,8	.62	15,7	.25	6,4	1.30	33,0		
5,6	USE-2	3	M3200GAH	LTCG LL 1/2	UL/CSA	.87	22,2	1.68	42,7	.44	11,2	.25	6,4	1.06	27,0

Skinned-Over Break-thru Solar Masthead Gland - Assembled Metal Locknuts INCLUDED															
5,5	USE-2	5	M3234GBR-SM	SMCG 3/4	UL/CSA	1.04	26,4	2.00	50,8	.62	15,7	.25	6,4	1.30	33,0
		9	M8437GBK-SM	SMCG 1		1.33	33,8	2.41	61,2	.76	19,3	.30	7,6	1.73	43,9
		13	M4524GBM-SM	SMCG 1-1/4		1.68	42,7	2.69	68,3	.78	19,8	.30	7,6	2.05	52,1
		21	M3317GBQ-SM	SMCG 1-1/2		1.92	48,8	2.81	71,4	.76	19,3	.36	9,1	2.48	63,0
		31	M3321GBY-SM	SMCG 2		2.40	60,8	2.92	74,2	.79	20,1	.42	10,7	2.73	69,3
5,6	USE-2	3	M3200GAH-SM	SMCG LL 1/2	UL/CSA	.87	22,2	1.68	42,7	.44	11,2	.25	6,4	1.06	27,0
7,7	PV 1000 or USE-2**	3	M3234GBS-SM	SMCG 3/4	UL/CSA	1.04	26,4	2.00	50,8	.62	15,7	.25	6,4	1.30	33,0
		5	M8437GBT-SM	SMCG 1	1.33	33,8	2.41	61,2	.76	19,3	.30	7,6	1.73	43,9	
		9	M4524GBW-SM	SMCG 1-1/4	1.68	42,7	2.69	68,3	.78	19,8	.30	7,6	2.05	52,1	
		11	M3317GBZ-SM	SMCG 1-1/2	1.92	48,8	2.81	71,4	.76	19,3	.36	9,1	2.48	63,0	
		19	M3321GBX-SM	SMCG 2	2.40	60,8	2.92	74,2	.79	20,1	.42	10,7	2.73	69,3	
8,9	PV 1000	7	M4524GCJ-SM	SMCG 1-1/4	UL/CSA	1.68	42,7	2.69	68,3	.78	19,8	.30	7,6	2.05	52,1
		9	M3317GCK-SM	SMCG 1-1/2	UL/CSA	1.92	48,8	2.81	71,3	.76	19,3	.36	9,1	2.48	63,0
		12	M3321GCM-SM	SMCG 2	UL/CSA	2.40	60,8	2.93	74,3	.79	20,1	.42	10,7	2.75	69,9

NEW!

Other Configurations with Approval Potential - Locknuts not included															
6,0	***	2	M3200GAJ	LTCG LL 1/2	-	.87	22,2	1.68	42,7	.44	11,2	.25	6,4	1.06	27,0
		4	M3234GBC	LTCG 3/4	-	1.04	26,4	2.00	50,8	.62	15,7	.25	6,4	1.30	33,0
6,5	***	6	M8437GAL	LTCG 1	-	1.33	33,8	2.41	61,2	.76	19,3	.30	7,6	1.73	43,9
			M4524GAL	LTCG 1-1/4	-	1.68	42,7	2.69	68,3	.78	19,8	.30	7,6	2.05	52,1
7,0	PV 1000	3	M3234GAM	LTCG 3/4	-	1.04	26,4	2.00	50,8	.62	15,7	.25	6,4	1.30	33,0
7,4	PV 1000	2	M3234GAN	LTCG 3/4	-	1.04	26,4	2.00	50,8	.62	15,7	.25	6,4	1.30	33,0

*AWG 10 and 12 for both USE-2 and PV 1000 except 4,5 mm Conductors Recognized for AWG 12 only.
 **8 AWG USE-2 Wire
 ***Depends on actual wire: 10 AWG USE-2 or 12 AWG PV 1000.
 For Locknut specifications or to order Locknuts separately, see pages 3-39 & 3-40.



Use Heyco Multi-Hole Cordgrips with Heyco Female Threaded Couplings and Heyco-Flex III Tubing to insulate exposed PV wiring when making complete liquid tight connections to solar combiner or inverter enclosures. See page 2-16 for details.

Quick Specs

Material	Nylon 6/6 with TPE sealing gland
Certifications	UL Listed under Underwriters' Laboratories File E51579 CSA Recognized under the Component Program of Underwriters' Laboratories File E51579 to both Canadian and U.S. requirements SR Certified by the Canadian Standards Association File 93876
Flammability Rating	94-V2
Temperature Rating	-22°F (-30°C) to 212°F (100°C)
IP Rating	IP 68

AMEYA360

Components Supply Platform

Authorized Distribution Brand :



Website :

Welcome to visit www.ameya360.com

Contact Us :

➤ Address :

401 Building No.5, JiuGe Business Center, Lane 2301, Yishan Rd
Minhang District, Shanghai , China

➤ Sales :

Direct +86 (21) 6401-6692

Email amall@ameya360.com

QQ 800077892

Skype [ameyasales1](#) [ameyasales2](#)

➤ Customer Service :

Email service@ameya360.com

➤ Partnership :

Tel +86 (21) 64016692-8333

Email mkt@ameya360.com