

Surface Mount 1227.60MHz SAW Filter

AFS20A20-1227.60-T3

Moisture Sensitivity Level (MSL) – This product is Hermetically Sealed and not Moisture Sensitive - MSL = N/A: Not Applicable



RoHS/RoHS II compliant



2.0 x 1.6 x 0.75 mm

FEATURES:

- 2.0 x 1.6 x 0.75 mm low profile SMT package
- Low Insertion loss
- Excellent selectivity with high out-of-band rejection

APPLICATIONS:

- Wireless Communication
- Remote Control
- Cellular Phones

ELECTRICAL SPECIFICATIONS:


Maximum Ratings

Item	Value
Input Power Level	+20 dBm max.
DC Permissive Voltage	3V DC max.
Operating Temperature Range	-55°C to + 105°C
Storage Temperature Range	-55°C to + 105°C

Parameters	Minimum	Typical	Maximum	Units	Notes
Center Frequency (f_c)		1227.60		MHz	
Insertion Loss (IL)		2.60	3.00	dB	
3dB Bandwidth	20	42		MHz	
Amplitude Ripple		0.80	2.00	dB	1217.60 ~ 1237.6MHz
Group Delay		12	26	ns	1217.60 ~ 1237.6MHz
Group Delay Ripple		23	70	ns	1217.60 ~ 1237.6MHz
Worst-Case Input / Output Return Loss	8.0	10.5		dB	1217.60 ~ 1237.6MHz
Stop-band Attenuation (Referenced to 0.0 dB)	15	20		dB	300MHz ~ 1152MHz
	15	20			1302MHz ~ 1900MHz
	15	21			1900MHz ~ 3000MHz
Source Impedance (Z_s)		50		Ω	See note # 1
Load Impedance (Z_L)		50		Ω	See note # 1

Note #1: No matching network required for operation into 50 Ω 's

TEST CIRCUIT:



Surface Mount 1227.60MHz SAW Filter

AFS20A20-1227.60-T3




RoHS/RoHS II compliant




2.0 x 1.6 x 0.75 mm


OUTLINE DIMENSION:



Recommended Land Pattern:



FILTER FREQUENCY RESPONSE (NARROWBAND)



Surface Mount 1227.60MHz SAW Filter

AFS20A20-1227.60-T3




RoHS/RoHS II compliant




2.0 x 1.6 x 0.75 mm


FILTER FREQUENCY RESPONSE (WITH-IN-PASSBAND)





FILTER FREQUENCY RESPONSE (WIDEBAND)




AFS20A20-1227.60-T3



REFLOW PROFILE:

**Packaging: 3,000 Units Per Reel**

Reel Dimensions



Dimensions: mm

ATTENTION: Abracon Corporation's products are COTS – Commercial-Off-The-Shelf products; suitable for Commercial, Industrial and, where designated, Automotive Applications. Abracon's products are not specifically designed for Military, Aviation, Aerospace, Life-dependant Medical applications or any application requiring high reliability where component failure could result in loss of life and/or property. For applications requiring high reliability and/or presenting an extreme operating environment, written consent and authorization from Abracon Corporation is required. Please contact Abracon Corporation for more information.



ABRACON CORPORATION

tel 949-546-8000 | fax 949-546-8001 | www.abracon.com

Revised: 02.16.15

AMEYA360

Components Supply Platform

Authorized Distribution Brand :



Website :

Welcome to visit www.ameya360.com

Contact Us :

➤ Address :

401 Building No.5, JiuGe Business Center, Lane 2301, Yishan Rd
Minhang District, Shanghai , China

➤ Sales :

Direct +86 (21) 6401-6692
Email amall@ameya360.com
QQ 800077892
Skype ameyasales1 ameyasales2

➤ Customer Service :

Email service@ameya360.com

➤ Partnership :

Tel +86 (21) 64016692-8333
Email mkt@ameya360.com