


1

2

3

4

FCI PART NO.	P/N	EC NO.	LENGTH	REV	ECN NO	DESCRIPTION
10109832-Z0400YYLF	73Y1189	N21913	4000+50/-0	D	ELX-N-22283-1	CHANGE THE LABEL PRINT
10109832-Z0200YYLF	73Y1108	N21913	2000+50/-0			



PIN ASSIGNMENT

P1	SIGNAL NAME	WIRE COLOR	WIRE AWG	P2
1	+5V	RED	20	3
2	-DATA	WHITE	28 *	6
3	+DATA	GREEN	28 *	4
4	GROUND	BLACK	20	5
SHELL	FRAME GND	BRAID		SHELL

*TWISTED PAIR

1	EA	ADHESIVE LABEL	5
A/R	KG	OVERMOLD PVC, 94V-0, PEBBLE GRAY (IBM CODE 43-4216)	4
A/R	M	USB 2.0 CABLE: UL(CM) CSA(CMG), 28AWG*1P+20AWG*2C+AL/MYLAR+DRAIN+BRAID, PEBBLE GRAY (IBM 43-4216)	3
1	EA	USB A TYPE PLUG. CONTACT PLATING: 30u" Au 50u" Ni Min.	2
1	SET	2x4 LATCH-N-LOK 360° SHIELDED PLUG CONNECTOR KIT <24V> KEY POSITION 2, COLOR:GRAY, FCI P/N:98028-7092LF	1
Q'TY	UNIT	DESCRIPTION	ITEM

spec ref	See Notes	dr	Carl Wang	2015-10-08	projection	MM	size	A3	scale	N/A
tolerance std	TOLERANCES UNLESS OTHERWISE SPECIFIED	eng	Carl Wang	2015-10-08	chr	Guo-Feng Jin	2015-10-08	ecn no		
		appr	Guo-Feng Jin	2015-10-08	product family		rel level			
surface	linear	0.X	±		FCI	title	USB A TYPE TO 2x4 LATCH-N-LOK CABLE ASSEMBLY	dwg no	10109832	rev
		0.XX	±							D
		0.XXX	±							
	angular	0°	±°		www.fci.com	cat. no.		Product - Customer Drw	sheet 1 of 2	

FCI PART NO.

SEE SHEET 1

NOTES:

1. 2x4 LATCH-N-LOK MATES WITH FCI PART NUMBER:
74355-XY2LF OR 87316-XY2LF.

2. UNLESS OTHERWISE SPECIFIED ASSEMBLED LENGTH TOLERANCE:
=< 1 METER= $\pm 15.0\text{mm}$
> 1 METER TO 10 METER= $\pm 2\%$ OF L1 OR L2
> 10 METER= $+0\%/-4\%$ OF L1 OR L2

3. PART NUMBER SCHEME FOR CABLE ASSEMBLY:

10109832 - Z X X X X Y Y LF

LF: LEAD FREE

NOT APPLICABLE TO THIS ASSEMBLY

NOT APPLICABLE TO THIS ASSEMBLY

LENGTH (METERS & CENTIMETERS)

0400: 4 METERS 00 CENTIMETERS

0200: 2 METERS 00 CENTIMETERS

WIRE GAGE

Z: MULTIPLE WIRE GAGE

4. UNLESS OTHERWISE SPECIFIED LABEL POSITION SHALL BE APPROXIMATELY
60mm FROM REAR OF CONNECTOR.

5. LABEL SHOULD BE PRINTED WITH BLACK TEXT AS SHOW BELOW:

P/N: 73Y11XX
EC NO: N21913
FCI
MADE IN CHINA
WWYY

--- P/N
--- EC NUMBER
--- SUPPLIER NAME
--- COUNTRY OF ORIGIN
--- DATE CODE WWYY FORMAT

7

6. ALL CABLE ASSEMBLIES SHALL BE TESTED 100% FOR CONTINUITY
AS DEFINED IN WIRING LIST.

7. UNLESS OTHERWISE SPECIFIED ALL CABLE ASSEMBLIES SHALL BE
100% HI-POT TESTED: DC 300V/10ms

8. OTHER ELECTRICAL SPECIFICATIONS:

DIELECTRIC RESISTANCE: 50M Ohms MIN.

CONNECTION RESISTANCE: 1.8 Ohms MAX. (For -Z0400YYLF, 4MR LENGTH)

CONNECTION RESISTANCE: 1.2 Ohms MAX. (For -Z0200YYLF, 2MR LENGTH)

9. THIS DIMENSION IS A FINISHED PRODUCT LENGTH.

10. LEAD FREE PRODUCTS MEET EUROPEAN UNION DIRECTIVES AND OTHER COUNTRY
REGULATIONS AS DESCRIBED IN GS-22-008.

11. CONNECTOR ASSEMBLIES SHOWN ARE FOR REFERENCE ONLY AND MAY
NOT SHOWN ALL PART DETAIL, REFERENCE CONNECTOR ASSEMBLY DRAWINGS
FOR COMPLETE DETAILS.

12. CABLE ASSEMBLY MUST WITHSTAND 66.7N (15 LB) PULL FORCE IN ANY DIRECTION
WITHOUT DAMAGE WHILE PLUGGED.

13. PACKAGE: EACH CABLE ASSEMBLY IN CLEAR ZIP-LOCK BPLY BAG,
LABEL (WHITE BACKGROUND WITH BLACK LETTERS, CONTENT SEE BELOW) TO BE
STAMPED ON CLEAR ZIP-LOCK POLY BAG, THEN BULK PACKED IN A BOX.

Mfg. Date: YYYY-MM-DD	
(P) FRU P/N: 73Y11XX	
EC: N21913	FCI
Quantity: 1	(4L) CoO: CN
Made in China	

CODE READ: P73Y11XX

CODE READ: 4LCN

spec ref		See Notes		dr	Carl Wang	2015-10-08			size	A3	scale	N/A
tolerance std	TOLERANCES UNLESS OTHERWISE SPECIFIED			eng	Carl Wang	2015-10-08			ecn no			
				chr	Guo-Feng Jin	2015-10-08						
				appr	Guo-Feng Jin	2015-10-08			product family		rel level	
surface	linear	0.X	±		title	USB A TYPE TO 2x4 LATCH-N-LOK CABLE ASSEMBLY		dwg no	10109832		rev	D
		0.XX	±									
		0.XXX	±									
	angular	0°	±°	www.fci.com	cat. no.	Product - Customer Drw				sheet 2 of 2		

AMEYA360

Components Supply Platform

Authorized Distribution Brand :



Website :

Welcome to visit www.ameya360.com

Contact Us :

➤ Address :

401 Building No.5, JiuGe Business Center, Lane 2301, Yishan Rd
Minhang District, Shanghai , China

➤ Sales :

Direct +86 (21) 6401-6692

Email amall@ameya360.com

QQ 800077892

Skype ameyasales1 ameyasales2

➤ Customer Service :

Email service@ameya360.com

➤ Partnership :

Tel +86 (21) 64016692-8333

Email mkt@ameya360.com